



VIEW

## Century

### COREtec® ProPlus

### COREtec® Floors

<http://www.coretecfloors.com> | [info@usfloors.be](mailto:info@usfloors.be)

**Type:** Vinyl | Wood decor

Laying type: Wild / Random bond

Looking for a floor that can take a beating? With its impact-resistant core and minimalist finish, ProPlus is an excellent choice for commercial spaces, such as stores and gyms.

mtextur ID	106700
Manufacturer	COREtec® Floors
Manufacturer-Email	info@usfloors.be
Product Line	COREtec® ProPlus
Product Line Info	Looking for a floor that can take a beating? With its impact-resistant core and minimalist finish, ProPlus is an excellent choice for commercial spaces, such as stores and gyms.
Material Name	Century
Type	Vinyl / Wood decor
Material Info	Laying type: Wild / Random bond
eBKP	G 2.2 Bodenbelag / G 2.2 Finished floor coverings
IFC	IfcCovering / IfcSlab.Floor
Area of application (mtextur Classic)	Inside / Floor
Delivery zones	CH / DE / LU / NL / FR / IT / AT / BE / ES / PT / SE / NO / FI / NZ / PL / SK / LI / MC
Size of the CAD & BIM texture	Height: 4758.0 mm / Width: 4880.0 mm

#### IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.

max. Length / Format	Length = 1220 mm / Width = 183 mm / Thickness = 5 mm
Quality	COREtec® Pro Core
Weight	8.23 kg/m²
Thermal Conductivity	0.0318 W/mK
Fire protection class	Bfl - S1 (EN 13501)
Light reflectance value	> grade 6 (ISO 105-B02)
Dimension tolerance length/width	Pass ≤ 0.25% (EN ISO 23999) mm
Sound absorption	17.0 α <sub>w</sub>
Lightfastness	> grade 6 (ISO 105-B02)
Characteristics Info	Klick-Vinyl, Vinyl, Klick-Boden, Kork (dank Unterlage), LVT, Fliese, Fliesenböden, Keramikböden

## IMPORTANT LEGAL INFORMATION FOR USAGE OF THE MTEXTUR-DATABASE AND MTEXTUR DATASHEET:

In the mtextur-database and the mtextur-datasheet you can find a variety of high-quality digitalized materials, classified according material-type and subtype, color scope, field of application, manufacturer and product-line. The liability of the colors and the pattern of a CAD-texture can not always be guaranteed. For binding samples and additional questions please get in contact with the manufacturer or reseller directly (request link on material page). The information found on the mtextur-database is carefully collected and tested. Nevertheless are there possibilities for mistakes or wrong information. The publisher, h2c GmbH, the according manufacturers and resellers are not liable for any missing or incorrect information and its outcome, except h2c GmbH acts insofar willful.